

CABLE TIES

● LOCKING CABLE TIES



(*)Suffix "-WR" should be added if black(outdoor) color is required.

2.5 TIE BODY WIDTH	PART NO	Length mm (inch)	Width mm (inch)	Max Bundle Dia,(inch)	Tensile Strength Kg(LBS)	Military Standard Spec,	Installation TOOL Part No	Package Q' ty
		DACT 80-2.3-L	80 (3.1)	2.4 (.09)	17 (.68)	8.1 (18)	MS3367-4	DAG-50
DACT100-2.5-L		100 (4.0)	21 (0.83)					
DACT160-2.5-L		160 (6.2)	2.5 (.10)	40 (1.57)				
DACT200-2.5-L		205 (8.0)		52 (2.02)				
3.6 TIE BODY WIDTH	DACT140-3.6-L	146 (5.7)	3.6 (.14)	35 (1.38)	17.8 (40)	MS3367-5	DAG-50	1,000
	DACT200-3.6-L	203 (8.0)		50 (2.00)				
	DACT210-3.6-L	210 (8.26)		52 (2.04)				
	DACT300-3.6-L	300 (11.8)		77 (3.03)				
	DACT370-3.6-L	370 (14.5)		102 (4.00)				

● LOCKING CABLE TIES



(*)Suffix "-WR" should be added if black(outdoor) color is required.

4.8 TIE BODY WIDTH	PART NO	Length mm (inch)	Width mm (inch)	Max Bundle Dia,(inch)	Tensile Strength Kg(LBS)	Military Standard Spec,	Installation TOOL Part No	Package Q' ty
		DACT120-4.8-L	120 (4.7)	4.8 (.19)	30 (1.00)	22.2 (50)	MS3367-1	DAG-50
DACT160-4.8-L		160 (6.2)	40 (1.57)		"			
DACT190-4.8-L		190 (7.5)	48 (1.89)		"			
DACT200-4.8-L		200 (8.0)	52 (2.05)		"			
DACT250-4.8-L		250 (10.0)	67 (2.64)		"			
DACT280-4.8-L		280 (11.0)	76 (2.99)		MS3367-7			
DACT300-4.8-L		300 (11.8)	83 (3.27)		MS3367-7			
DACT370-4.8-L		368 (14.5)	102 (4.02)		MS3367-2		500	

Material : Nylon 66
 Color : Natural or Black(UV)
 Flammability : UL 94V-2 or UL94 V-0
 Service Temperature : 85 °C



Most **Dong-A Cable Ties**, when tested, meet the requirements of **MIL-S-23190E** (or **SAE AS23190**)

CABLE TIES

● LOCKING CABLE TIES




(*)Suffix "-WR" should be added if black(outdoor) color is required.

6.3 TIE BODY WIDTH	PART NO	Length mm (inch)	Width mm (inch)	Max Bundle Dia,(inch)	Tensile Strength Kg(LBS)	Military Standard Spec,	Installation TOOL Part No	Package Q' ty
	DAMCT270-6.1-L	279 (10.5)	6.1 (.24)	73 (2.87)		MS3367-3	DAG-250	500
	DAMCT300-6.3-L	300 (11.8)	6.3 (.24)	80 (3.15)	45.3 (100)			300
	DAMCT370-6.3-L	370 (14.5)	6.3 (.24)	102 (4.02)				
	DAMCT200-7.6-L	200 (8.0)		50 (2.00)		MS3367-3	DAG-250	500
	DAMCT300-7.6-L	300 (11.8)	7.6 (.30)	78 (3.07)	53.4kg (120)			300
	DAMCT370-7.6-L	370 (14.5)		102 (4.02)				

● LOCKING CABLE TIES



(*)Suffix "-WR" should be added if black(outdoor) color is required.

9.0 TIE BODY WIDTH	PART NO	Length mm (inch)	Width mm (inch)	Max Bundle Dia,(inch)	Tensile Strength Kg(LBS)	Military Standard Spec,	Installation TOOL Part No	Package Q' ty
	DAMCT450-9.0-L	455 (17.7)		127 (5.0)		MS3367-6	DAG-250	100
	DAMCT530-9.0-L	530 (20.9)		152 (6.0)				
	DAMCT650-9.0-L	650 (25.6)	9.0	188 (7.40)	77.8 (175)			
	DAMCT780-9.0-L	780 (30.6)	(.35)	225 (8.86)				
	DAMCT880-9.0-L	880 (34.6)		260 (10.24)				
	DAMCT1000-9.0-L	1000 (42.5)		320 (12.69)				

Material : Nylon 66
 Color : Natural or Black(UV)
 Flammability : UL 94V-2 or UL94 V-0
 Service Temperature : 85 °C

Most **Dong-A Cable Ties**, when tested, meet the requirements of **MIL-S-23190E** (or **SAE AS23190**)