



# CABLE TIES

## EXTRA HEAVY LASHING TIES



Available only in Natural Color or Weather Resistant Black.


(\* )Suffix "-WR" should be added if black(outdoor) color is required.

12.7 TIE BODY WIDTH	PART NO	Length mm (inch)	Width mm (inch)	Max Bundle Dia, (inch)	Tensile Strength Kg(LBS)	Military Standard Spec,	Installation TOOL Part No	Package Q' ty
	LOCKING TYPE  Loop on the head Type	DAL300-12.7-L	300 (11.8)	12.7 (.50)	70 (2.76)	110 (250)	MS3367-6	DAG-250
DAL400-12.7-L		400 (15.7)	102 (4.02)					
DAL540-12.7-L		540 (21.3)	150 (5.91)					
DAL780-12.7-L		780 (30.7)	220 (8.66)					
RELEASABLE TYPE  DARCT	DARCT300-12.7-L	300 (11.8)	12.7 (.50)	70 (2.76)	110 (250)	MS3367-6	DAG-250	100
	DARCT400-12.7-L	400 (15.7)		102 (4.02)				
	DARCT540-12.7-L	540 (21.3)		150 (5.91)				
	DARCT780-12.7-L	780 (30.7)		220 (8.66)				



Available only in Natural Color or Weather Resistant Black.

(\* )Suffix "-WR" should be added if black(outdoor) color is required.

12.7 TIE BODY WIDTH	PART NO	Length mm (inch)	Width mm (inch)	Max Bundle Dia, (inch)	Tensile Strength Kg(LBS)	Military Standard Spec,	Installation TOOL Part No	Package Q' ty
	LOCKING TYPE  DAL	DAL300-12.7-L	300 (11.8)	12.7 (.50)	70 (2.76)	110 (250)	MS3367-6	DAG-250
DAL400-12.7-L		400 (15.7)	102 (4.02)					
DAL540-12.7-L		540 (21.3)	150 (5.91)					
DAL780-12.7-L		780 (30.7)	220 (8.66)					

※ 내한성(耐寒性) 재질 발주시는 "LT" 추가,  
 내열성(耐熱性) 재질 발주시는 "HR" 추가,  
 내후성(耐候性) 재질 발주시는 "WR" 추가 표시 바랍니다.  
 (i.e) 내한성 : DAL400-12.7-LT  
 내열성 : DAL300-12.7-HR  
 내후성 : DAL300-12.7-LWR  
 Service Temperature : 85°C

Most Dong-A Cable Ties, when tested, meet the requirements of MIL-S-23190E (or SAE AS23190)

# CABLE TIES

## ● NYLON12 CABLE TIES



	PART NO	Length mm (inch)	Width mm (inch)	Max Bundle Dia,(inch)	Tensile Strength Kg(LBS)	Installation TOOL Part No	Package Q' ty
<b>3.6</b> TIE BODY WIDTH	DACT-N12-140-3.6	146 (5.7)	3.6 (0.14)	35 (1.38)	11.3 (25)	DAG-50	1,000
	DACT-N12-200-3.6	200 (5.7)		50 (2.00)			
<b>4.8</b> TIE BODY WIDTH	DACT-N12-190-4.8	190 (7.5)	4.8 (.19)	48 (1.89)	18.1 (40)	DAG-50	1,000
	DACT-N12-200-4.8	200 (5.7)		50 (2.00)			
	DACT-N12-300-4.8	201 (11.8)		83 (3.27)			500
<b>7.6</b> TIE BODY WIDTH	DACT-N12-300-7.6	300 (11.8)	7.6 (0.30)	78 (3.07)	40.8 (90)	DAG-250	100
	DACT-N12-370-7.6	370 (14.5)		102 (4.02)			
<b>9.0</b> TIE BODY WIDTH	DACT-N12-450-9.0	455 (17.7)	9.0 (.35)	127 (5.00)	53.4 (120)	DAG-250	100
<b>12.7</b> TIE BODY WIDTH	DACT-N12-400-12.7	400 (15.7)	12.7 (0.5)	102 (4.02)	77.8 (175)	DAG-250	50
	DACT-N12-540-12.7	540 (21.3)		150 (5.91)			

Material : Nylon 12

Excellent resistance to UV(ultraviolet), Overall Chemicals (hydrocarbons, chlorinated hydrocarbons, Acids, Bases) and Salts

## ● STAINLESS STEEL LOCK-KEY CABLE TIE



	PART NO	Length mm (inch)	Width mm (inch)	Max Bundle Dia,(inch)	Tensile Strength Kg(LBS)	Installation TOOL Part No	Package Q' ty
<b>3.6</b> TIE BODY WIDTH	DSLTL 155-3.6	155 (6.1)	3.6 (0.14)	38 (1.5)	17.8 (40)	DAG-50	1,000
	DSLTL 203-3.6	203 (8.0)		51 (2.0)			
<b>4.7</b> TIE BODY WIDTH	DSLTL 203-4.7	203 (8.0)	4.7 (0.185)	51 (2.0)	22.2 (50)	DAG-50	1,000
	DSLTL 305-4.7	305 (12.0)		77 (3.0)			
<b>7.0</b> TIE BODY WIDTH	DSLTL 300-7.0	300 (11.8)	7.0 (0.275)	77 (3.0)	53.4 (120)	DAG-250	100
	DSLTL 378-7.0	378 (14.9)		102 (4.0)			

Material : 66 Nylon

Color : Natural or Black(colors are available upon request)

Flammability : UL 94V-2 or UL94V-0

Service Temperature : 85 °C

(\* )Suffix "-BK" should be added if black color is required.

Suffix "-LWR" should be added if weather resistance is required.

